

| Parameter               | Reportable Range    | Resolution | Measurement method    |
|-------------------------|---------------------|------------|-----------------------|
| pH (pH units)           | 6.5 – 8.0           | 0.001      | Potentiometric sensor |
| pO2 (mmHg)              | 10 – 700            | 0.1        | Amperometric sensor   |
| pCO <sub>2</sub> (mmHg) | 10 – 150            | 0.1        | Potentiometric sensor |
| Na (mmol/L)             | 100 – 180           | 0.1        | Potentiometric sensor |
| K (mmol/L)              | 2.0 - 9.0           | 0.01       | Potentiometric sensor |
| Ca (mmol/L)             | 0.25 – 2.5          | 0.01       | Potentiometric sensor |
| CI (mmol/L)             | 65 – 140            | 0.1        | Potentiometric sensor |
| Glu (mg/dL or mmol/L)   | 20 - 700\1.1 - 38.9 | 1/0.1      | Amperometric sensor   |
| Lac (mg/dL or mmol/L)   | 2.7 – 180.2\0.3 -20 | 0.1/0.01   | Amperometric sensor   |
| Hct (%PCV or Fraction)  | 10 - 75\0.10 - 0.75 | 1%/0.01    | Conductance sensor    |

#### **Specification**

| Throughput            | Results in 1 minute after sample aspiration                             |  |  |  |  |
|-----------------------|-------------------------------------------------------------------------|--|--|--|--|
| Sample volume         | 140µl                                                                   |  |  |  |  |
| Quality control       | 3 or 5 levels QC, External electronic simulator                         |  |  |  |  |
| Display               | 7-inch color LCD Display, 800*480                                       |  |  |  |  |
| Interface             | 4 x USB 2.0 host, 1 x RS232, WLAN                                       |  |  |  |  |
| Input device          | Touch screen and barcode scanner                                        |  |  |  |  |
| Power supply          | 100~240VAC, 50/60Hz                                                     |  |  |  |  |
| Battery               | 4200mAh rechargeable lithium-ion battery, 50 samples continuous testing |  |  |  |  |
| Dimensions (W*H*D)    | 238*153*310 mm                                                          |  |  |  |  |
| Weight                | 3.65 KG                                                                 |  |  |  |  |
| Operation Environment | 10 °C-31 °C; %RH: 25%-80%; 70 -106.6 KPa                                |  |  |  |  |

#### About Edan

Edan is a healthcare company dedicated to improving the human condition around the world by delivering value-driven, innovative and high-quality medical products and services. For over 20 years, Edan has been pioneering a comprehensive line of medical solutions that address a broad range of healthcare practices including:

- Diagnostic ECG
- Ultrasound Imaging
- In-Vitro Diagnostics

- Patient Monitoring
- Point-of-Care Testing
- Veterinary

• OB/GYN

Healthcare professionals around the world depend on Edan's breakthrough medical technologies and outstanding customer support.



#### Global Headquarters:

Edan Instruments, Inc. | 15 Jinhui Road, Pingshan District, Shenzhen 518122 P.R. China | +86.755.26898326 | www.edan.com | info@edan.com U.S. and Canada inquiries:

EDAN Diagnostics, Inc. | 9918 Via Pasar, San Diego, CA 92126

+1.858.750.3066 | www.edandiagnostics.com | edan-info@edandiagnostics.com

© Edan Instruments, Inc. All rights reserved. Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



# i15 VET

Veterinary Blood Gas and Chemistry Analyzer





LAN/Wi-Fi connectivity

Build-in Printer and USB Storage











i15 trailer

#### Portable, lightweight

- Capable to run 50 samples with fully-charged battery
- Diagnose at the point of care, patient side, out in the field or exam room

#### Easy, Quick and Convenient

- Zero maintenance
- Minimize hands on time and training requirement
- Auto-sampling
- Report is ready within one minute after sample aspiration

#### Accurate and Reliable

- Innovative microchip liquid control technology and micro-sensor multifunction membrane technology
- High sensitivity and accuracy
- Calibrator, Control and Electronic simulator to TRIPLE guarantee the RESULTS!

#### Flexible Data Management


- Acquire patients' information via barcode/QR code
- Up to 10,000 patient data storage
- 4 USB ports and LAN/WiFi for data management
- Optional data management software

#### Multi-parameter cartridge

- Multi popular time-sensitive parameters come in one cartridge, including ABG, electrolytes and metabolites
- Single-use cartridge avoids contamination
- Room temperature storage with long shelf-life



Touch screen with built-in multimedia tutorials



## **i15 VET**

Veterinary Blood Gas and Chemistry Analyzer

i15 VET Quality Control System
Triple Guarantee the Result





### Variety of Veterinary test Cartridges

| varioty or votormary tool cartriagos |    |                  |                 |  | Hct |  |  |
|--------------------------------------|----|------------------|-----------------|--|-----|--|--|
|                                      | рН | pCO <sub>2</sub> | pO <sub>2</sub> |  |     |  |  |
| BG3                                  |    |                  |                 |  |     |  |  |
| BG8                                  |    |                  |                 |  |     |  |  |
| BG4                                  |    |                  |                 |  |     |  |  |
| BG9                                  |    |                  |                 |  |     |  |  |
| BG10                                 |    |                  |                 |  |     |  |  |
| BC4                                  |    |                  |                 |  |     |  |  |